















## Miscellaneous

Adapter plates sized			50 x 50 mm	50 x 50 mm	54 x 54 mm	60 x 60 mm
Illustration	Model	Connection	Aluminium	Stainless steel	Aluminium	Aluminium
	Faceplate (half size) Faceplate (full size)		7444 000 400 7444 000 500	7451 000 400 7451 000 500	7441 000 400 7441 000 500	7442 000 400 7442 000 500
	Mains switch (full size plate) only available pre-mounted in desktop casings		7444 000 200	7451 000 200		
	Faceplate with cable outlet for cables up to 12 or 9 mm diameter		7444 000 444	7451 000 444		
	Push-button, stainless steel, 48 VDC / 125 mA e.g. for control of selectors (e.g. No. 5816 000 007) with contact inputs	Soldering	7444 000 441	7451 000 441		
	Button, stainless steel 30 V DC / 500 mA	Soldering	7444 000 442	7451 000 442		
	Push-button, stainless steel with blue LED, 48 VDC / 500 mA, with light ring 9 - 12 V DC, 1 x open / close	Soldering	7444 000 443	7451 000 443		
	Button panel, 8-fold with blue LEDs, 48 V DC / < 50 mA, light 12 - 24 V e.g. for switcher with contact inputs etc.	Screw+clamp	7444 000 445			

## Computer / video

Adapter plates sized			50 x 50 mm	50 x 50 mm	54 x 54 mm	60 x 60 mm
Illustration	Model	Connection	Aluminium	Stainless steel	Aluminium	Aluminium
	VGA (HD15) Required installation depth for cable+plug connection: 47 mm for clamp connection: 42 mm	Soldering Cable+plug Gender changer Clamp	7444 000 401 7444 000 501 7444 000 601 7444 000 701	7451 000 401 7451 000 501 7451 000 601	7441 000 401 7441 000 501 7441 000 701	7442 000 401 7442 000 501
	VGA to BNC 5 Required installation depth: 47 mm	Cable+plug	7444 000 507		7441 000 507	7442 000 507
	VGA active (full size plate) with integrated VGA amplifier 1:1; 400 MHz and with external power supply 230 V / 12 V DC Required installation depth: 40 mm	Cable+plug	7444 000 509	7451 000 509	7441 000 509	
	DVI-I (24 + 5 pin) Required installation depth: for cable+plug connection: 65 mm for clamp connection: 42 mm	Soldering Cable+plug Cable+plug	7444 000 402 7444 000 502 7444 000 702	7451 000 502	7441 000 402 7441 000 502 7441 000 702	7442 000 502
	HDMI Required installation depth: for cable+plug connection: 52 mm for clamp connection: 42 mm	Cable+plug Clamp	7444 000 540 7444 000 740	7451 000 540	7441 000 540 7441 000 740	7442 000 540
	DVI-D to HDMI Required installation depth: 52 mm	Cable+plug	7444 000 580		7441 000 580	
	HDMI to DVI Required installation depth: 52 mm	Cable+plug	7444 000 581		7441 000 581	