


FY-UV2200W


2.2M print width, only roll to roll Sophisticated technology in Simple design for Spectacular performance

FY-UV2200W





High-strength printhead plate, with options of different color matches available.



Double strengthful wallboard, extra large rubber without distortion.

Printhead Options:

roller





stable ink supply.

Technical Specifications

Model		i3		К3		R5S		R5		
Printhead		EPSON i3200		F printhead		RICOH G6		RICOH G5		
Print width			2200mm							
out Options	Sandwich white	Staggered colors	Sandwich white	Staggered colors	Sandwich white	Staggered colors	Sandwich white	Staggered colors		
4PASS	/	/	/	/	22m²/h	41m²/h	15m²/h	29m²/h		
6PASS	6.6m²/h	13m² /h	7.6m²/h	14.6m²/h	14m²/h	28m²/h	11m²/h	20m²/h		
8PASS	5m²/h	10m²/h	5.5m²/h	11m²/h	10m²/h	18m²/h	8m²/h	15m²/h		
Media width: 2300mm				Air Pressure Requirement : Positive 6kg						
Type: Vinyl, sticker, polyester, one-way vision, flex, banner in roll or sheet				Print Interface: USB 3.0						
Ink: UV Curable Ink				Printer: AC220V 50HZ 6.6A 1450W						
Ink supply system: Negative pressure ink supply				Print Platform Vacuum Hold Down Area: AC220V 50HZ 10A 2200W						
Curing method: LED UV Lamp				Operation Environment: Temperature 20°C-28°C Humidity40%-60%						
RIP: United Fancy				Printer Dimensions: L3955mm×W1035mm×H1500mm						
	6PASS 8PASS ker, polyester, one	EPSO out Options Sandwich white 4PASS / 6PASS 6.6m ² /h 8PASS 5m ² /h	EPSON i3200 out Options Sandwich white 4PASS / 4PASS / 6PASS 6.6m²/h 8PASS 5m²/h 10m²/h 23 ker, polyester, one-way vision, flex, banner in roll UV Cural n: Negative pressure ink s LED UV	EPSON i3200 F prin out Options Sandwich white Staggered colors Sandwich white 4PASS / / / 6PASS 6.6m²/h 13m²/h 7.6m²/h 8PASS 5m²/h 10m²/h 5.5m²/h 2300mm 2300mm ker, polyester, one-way vision, flex, banner in roll or sheet UV Curable Ink n: Negative pressure ink supply LED UV Lamp	EPSON i3200 F printhead 2200 out Options Sandwich white Staggered colors Sandwich white Staggered colors 4PASS / / / / / 6PASS 6.6m²/h 13m²/h 7.6m²/h 14.6m²/h 8PASS 5m²/h 10m²/h 5.5m²/h 11m²/h 2300mm Air Pressur Print Interf ker, polyester, one-way vision, flex, banner in roll or sheet Print Interf UV Curable Ink Print Platform Vac h: Negative pressure ink supply Print Platform Vac LED UV Lamp Operation Env	EPSON i3200 F printhead RICO 2200mm 2200mm out Options Sandwich white colors 4PASS / / / / / 22m²/h 6PASS 6.6m²/h 13m²/h 7.6m²/h 14.6m²/h 14m²/h 8PASS 5m²/h 10m²/h 5.5m²/h 11m²/h 10m²/h 2300mm Air Pressure Requirem Print Interface : Print Interface : UV Curable Ink Print Platform Vacuum Hold Down Are Operation Environment: Term	EPSON i3200 F printhead RICOH G6 2200mm 2200mm out Options Sandwich white Staggered colors Sandwich white Staggered colors 4PASS / / / / 22m²/h 41m²/h 6PASS 6.6m²/h 13m²/h 7.6m²/h 14.6m²/h 14m²/h 28m²/h 8PASS 5m²/h 10m²/h 5.5m²/h 11m²/h 10m²/h 18m²/h 2300mm Air Pressure Requirement : Print Interface : Print Interface : Print Interface : UV Curable Ink Print Platform Vacuum Hold Down Area: AC220N AC220N LED UV Lamp Operation Environment: Temperature 20	EPSON i3200 F printhead RICOH G6 RICO 2200mm 2200mm 2200mm Sandwich white Staggered colors Sandwich white Sandwich colors Sandwich white Sandwich white Sandwich colors Sandwich colors Sandwich colors Sandwich colors Sandwich colors Sandwi		

1. The speed data are taken from the printer at high speed, a difference of 10% may occur when running with different computers. 2. Product specifications are subject to change without notice in advance. Color and shape in picture are for reference, computer and monitor not included. All rights reserved!





Light box advertising









Add: No.1 Lane 19 Ganghe Rd.Xidu, Fengxian Dist Shanghai 201401, P.R.China Tel: +86-(0)21-67158920 67158921 Fax: +86-(0)21-67158922 Email: sales@fyunion.com Website: www.fyunion.com


Leather printing

Individually controlled negative pressure system for



New belt feeding system to feed elastic media





Pneumatically controlled feeding and take-up systems with extra large 260MM-diameter shaft.



Double silent guide, for speedy and stable carriage moving.



✓ Ricoh Gen 5 / Gen 6







Window advertising