











Data

Adapter plates sized			50 x 50 mm	50 x 50 mm	54 x 54 mm	60 x 60 mm
Illustration	Model	Connection	Aluminium	Stainless steel	Aluminium	Aluminium
	Serial RS232 (9-pin SubD)	Soldering Cable+plug	7444 000 420 7444 000 520	7451 000 420	7441 000 420 7441 000 520	7442 000 420 7442 000 520
	PS/2	Soldering Cable+plug	7444 000 521		7441 000 421 7441 000 521	
	USB (2.0 compatible) A-socket (f)/A-socket (f) Required installation depth: 43 mm	Cable+plug	7444 000 522	7451 000 522	7441 000 522	7442 000 522
	USB (2.0 compatible) B-socket (f)/A-socket (f) Required installation depth: 43 mm	Cable+plug	7444 000 525	7451 000 525	7441 000 525	7442 000 525
	USB - CAT 5 With integrated USB extender (No. 5772 000 001) for USB 1.1, Max. length CAT 5 cable between sender and receiver: 45 m	Cable+plug	7444 000 524		7441 000 524	

Network

Adapter plates sized			50 x 50 mm	50 x 50 mm	54 x 54 mm	60 x 60 mm
Illustration	Model	Connection	Aluminium	Stainless steel	Aluminium	Aluminium
	CAT 5 (RJ45) Gender changer (1:1)		7444 000 523	7451 000 523	7441 000 523	7442 000 523
	CAT 6/6A (RJ45) Socket (f) "Setec"	Cut+clamp	7444 000 423	7451 000 423	7441 000 423	7442 000 423
	CAT 6 (RJ45) Socket (f) "BTR"	Gender changer (1:1)	7444 000 526	7451 000 526	7441 000 526	7442 000 526
	CAT 6/6A (RJ45) Socket (f) "Rutenbeck" Flexible cable outlet for limited installation space Required installation depth: 26 mm	Cut+clamp	7444 000 425	7451 000 425	7441 000 425	
	CAT 7 Socket (f) "Nexans" Certified up to 1000 MHz downward compatible to RJ45 (CAT 5/CAT 6)	Cut+clamp	7444 000 424	7451 000 424	7441 000 424	7442 000 424