## KINDERMANN CEILING LIFT COMPACT 80/120 Compact ceiling lift with

## minimum installation height

The Kindermann ceiling lift Compact is extremely flat. For projectors of not more than 6.5 cm, e.g., a false ceiling of 12 cm (Compact 80) or 14 cm (Compact 120) is sufficient.

The Compact lift is easy to mount, and its mounting frame (Ref. No. 7466 000 010) fits into false ceilings with standardized ceiling elements of  $60 \times 60$  cm.

An integrated safety switch stops the lift on its way down when hitting an obstacle.

A power supply for the projector is pre-installed. A spiral cable guide guarantees safe power and data supply. There is a 4-pin connection control for mains (230 V) and up and down control.

The position of the projector can be easily fixed via a separate programming unit (Ref. No.  $7466\,000\,100/$  -101).

Ceiling lift Compact 80

- Lifting range up to 120 cm
- Max projector weight 20 kg
- Super flat universal projector holder
- Installation height > 12 cm
- Sturdy construction
- Easy mounting





## Technical data

	Ceiling ift Compact 80	Ceiling lift Compact 120	
Ref.No .	7466 000 000	7466 000 001	
Installationh eight	6 cm + projector height, min. 12 cm	8 cm + projector height, min. 14 cm	
Projectormou nting	universal projector mount (fixing points between 75 – 370 mm)		
Liftingr ange	up to 80 cm	up to 120 cm	
Weight of lifts	24 kg (without projector)	26 kg (without projector)	
Max.p rojectors ize	47 x 56 cm		
Max.p rojectorw eight	20 kg		
Powerc onsumption	220 W		
Voltage	230 V, 50 Hz		
Connection	4-pin (up/down/PE/N)		
Required ceiling space	69 x 73 cm		
Cutout of ceiling	60 x 50 cm		
Ceilingp late	optional accessory		
Colour	metallic silver, coated (RAL 9006)		

## Accessories for ceiling lifts Compact 80/120 (see page 72-73 for more accessories)

Illustration	Item	Specification	Ref.N o.
	Ceiling plate Standard	550 x 650 mm for covering the ceilng, white (RAL 9003)	7466 000 011
	Ceiling plate with T profile	For invisible mounting, integration of the ceiling cutout (500 x 600 mm) in the lift (RAL 9003)	7466 000 010
$\diamond$	Metalp anelling	For visible mounting of the lift on the ceiling, 4 parts, height ca. 35 cm, white (RAL 9003)	7466 000 020