

Nuvo®

12" Powered Subwoofer



The 12" Powered Subwoofer brings music, movies, and video games to life with an immersive bass experience that you can not only hear, but truly feel. With a front-mounted woofer and efficient all-digital 300 watt amplifier, the NV-SUB12GB adds a deep and detailed low-frequency impact to custom home theater or audio installations. Its sealed cabinet is constructed of durable MDF for a distortion-free, superior bass response.

- **Powerful front-mounted 12" subwoofer ideal for custom audio installations**
- **Efficient all-digital 300 watt amplifier**
- **Durable MDF enclosure construction ensures distortion-free bass response**
- **Unfiltered LFE (low frequency effects) input, RCA stereo input and output, and USB port**
- **Signal-sensing power ON/OFF**
- **Variable crossover and phase adjustment**
- **Woofer has lifetime warranty and amplifier has two year warranty**

The NV-SUB12GB features signal-sensing power activation (optional setting) to automatically turn on the subwoofer when it receives a signal from the receiver. It will return to standby after 15 minutes of no signal.

Offering maximum versatility, the Powered Subwoofers were designed to integrate with almost any audio system. Unfiltered LFE / RCA stereo input and output let you easily connect to most modern receivers. And a convenient USB jack can power an optional wireless receiver. The variable crossover and phase controls allow you to match the Subwoofer output with the main speakers for premium performance and sound.



Nuvo® NV-SUB12GB Subwoofer

Materials

Multiple-coat high-gloss painted cabinet

Output

Speaker Impedance	8 Ohms
Power Consumption	45 watts typical 360 watts max
Output Power	300 watts
Frequency	23Hz - 200Hz
Line Output Connector	RCA analog (pair)
Operating Temperature	5° - 35° C 41° - 95° F

Input

Line Input Connector	LFE / RCA analog (pair)
Input Voltage	110v - 220v (manual switch)
Line Input Overload	8 volts

Regulatory Approvals

cTUVus, CE-LVD
 US:FCC CFR Title 47 Part 15, Subpart B; CANADA:ICES-003
 EUROPE:CISPR32; EUROPE: EN 55032:2012;
 AUSTRALIA/NEW ZEALAND: RCM Standard AS/NZS CISPR32
 RoHS (Restriction of Hazardous Substances Directive 2002/95/EC)

Weight

Unit Weight (kg)	16.7 kg
Unit Weight (lbs)	36.8 lbs
Shipping Weight (kg)	20.9 kg
Shipping Weight (lbs)	46.1 lbs

Unit Size

Unit Size (mm)	388.6 L x 373.4 W x 406.4 H
Unit Size (inch)	15.3 L x 14.7 W x 16 H

Unit Size without feet

Unit Size (mm)	373.4 L x 373.4 W x 406.4 H
Unit Size (inch)	14.7 L x 14.7 W x 16 H

Shipping Specifications

Unit Size (mm)	525.8 L x 525.8 W x 533.4 H
Unit Size (inch)	20.7 L x 20.7 W x 21 H

Legrand reserves the right to change specifications without notice.



designed to be better™



Legrand, North America

3015 Kustom Drive
 Hebron, KY 41048
 United States
 844.334.8044
www.legrand.us/nuvo